

MOBIHEL[®]

... for the cars we love

FADE OUT THINNER 2400

It is used at painting of border zone between the repaired damage and old lacquering. In MOBIHEL 2K 2:1 clearcoat low VOC, which is ready for spraying we add MOBIHEL 2K fade out thinner 2400 in ratio 1:3 and we spray only border zone between the damaged part and old lacquering.

Distributed by:

Crest Cormix Pty. Ltd.

13 Newmarket Lane,

Epping, Victoria 3076.

Tel: +61 3 9945 2700

Fax: +61 3 9945 2799

Email: enquiries@crestcormix.com.au

Web: www.crestcormix.com.au

HELIOS TBLUS, d.o.o., Količevo 65, 1230 Domžale, Slovenija

T: +386 1 722 40 00, E: office@helios-refinish.com, www.mobihel-refinish.com



PACKING DATA**Packing:**
12 x 0.5 l**Index:**
47017331**HYGIENE & PERSONAL PROTECTION****TECHNICAL CHARACTERISTICS****Colour:** Colourless
Product type: Thinner
Density: 0,913 g/l**APPLICATION**

MOBIHEL Manual

SHELF LIFE**Shelf life:**

5 years

SAFETY ADVICE

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid release to the environment. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

ONLY FOR PROFESSIONAL USE