

ASP-50NS

Micronized polypropylene for adding texture, structure and non-slip properties for a wide variety of paints and coatings.

Features and Benefits

- Provides a consistent very fine smooth texture feel at coating surface, reducing mold (slip) formation in wet areas.
- Tough, high molecular weight polypropylene provides added film durability.
- Increases COF (coefficient slip resistance), ideal for glossy non-slip surfaces.
- Easy to disperse powder that can be incorporated with high speed mixing

Composition

Polypropylene

Recommended Addition Levels

3.0-10.0% (on total formula weight)

Systems and Applications

Water based, solvent based, industrial and consumer paints including masonry, stucco paints, architectural wall and trim paints; stains, sealers and varnishes; wood coatings; specialty floor coatings.

Typical Properties*

ASP50NS

Melting Point °C	166 - 168
Density @ 25 °C (g/cc)	0.9
Maximum Particle Size (µm)	297 50mesh)

Crest Cormix Pty Ltd

1/111 Lewis Road,
Knoxfield,
VICTORIA 3180

Ph: +61 3 9887 0422

Email: enquiries@crestcormix.com.au

www.crestcormix.com.au

The above data reflects typical properties. The information contained herein is to the best of our knowledge true and correct and any suggestions are made without guarantee, express or implied, since conditions of use are beyond our control. Crest Cormix Pty Ltd disclaims any liability incurred in connection with the use of any data or suggestions. Nothing contained herein shall be construed as a recommendation to infringe on any existing patents covering any material or its use.