

## Conpatch® NCI

### SURFACE APPLIED MIGRATING CORROSION INHIBITOR

#### DESCRIPTION

**Conpatch NCI** is a surface applied migratory corrosion inhibitor, designed to migrate even through dense concrete structures forming a protective layer on the surface of the reinforcement. **Conpatch NCI** can be used in reinforced concrete structures that show signs of reinforcement corrosion or need additional protection to inhibit future corrosion. It protects the steel by forming a protective layer and reduces the corrosion rate.

**Conpatch NCI** is applied to the surface and drawn into the concrete via capillary action. Additionally **Conpatch NCI** moves throughout the concrete pore structure following Fick's law, molecules move randomly in vapour phase through the cement matrix from areas of high concentration to areas of low concentration. Independent tests have shown that **Conpatch NCI** is adsorbed on to reinforcement at a depth of 7-8.5 cm forming a layer up to 100Å thick. Chlorides are shown to penetrate 60 mm. deep confirming the ability of **Conpatch NCI** to displace chlorides providing protection at the reinforcements surface despite the presence of chlorides.

The rate of migration is dependent on the density & permeability of the concrete and other factors, however, it is between 7-8 cm at 7 days.

#### USES & ADVANTAGES

Migratory corrosion inhibitor's are useful for repair and maintenance purposes and the treatment of undamaged concrete where corrosion induced damage is anticipated due to chloride or carbonation attack. **Conpatch NCI** extends the service life of the structure for below and above ground structures. It can be used for all type of buildings, marine structures, car parks, bridges, dams, water tanks, cooling towers, etc.



##### Advantages include:-

- Protection of concrete steel reinforced structures.
- Non staining.
- Low viscosity ensures good in depth penetration through capillary pores.
- Both delays, the start of corrosion and reduces the corrosion rate.
- Easy to apply and economical.
- Extension of service life and long term protection.
- Safe and environment friendly.
- Protects both cathodic and anodic areas.
- No special curing time required traffic can resume immediately after application.
- Water based and non flammable.
- Can perform on other metals such as galvanized steel, aluminum, coated steel.
- Use is combination with Contite waterproofing by crystallization for total concrete protection (rebar & cement paste).

#### PROPERTIES

<b>Form:</b>	Liquid
<b>Appearance:</b>	Yellow to Amber colour
<b>Density:</b>	1.10 ± 0.02 Kg/Ltr
<b>pH:</b>	9 to 11
<b>Flash Point:</b>	Not applicable (water based)
<b>Drying time:</b>	30 - 40 mins
<b>Re coat time:</b>	40 - 60 mins

Schematic Representation of **Conpatch NCI** by Vapour diffusion system and penetration through capillary pores.



#### SURFACE PREPARATION

Substrate should be dry, sound, clean and free of all dirt, grease, oil, laitance, sealers, coatings, curing compounds, membranes, etc. Cleaning can be done by use of mechanical equipment or by using jet water blast.

**APPLICATION**

Conpatch NCI can be applied either by using a brush, roller or low pressure spray equipment. For better performance at least 2 coats are required. Application should be done +5 to +30° C

Conpatch NCI can also be applied by using an injection method to ensure fast and deep penetration into thick structures and speeding up work.

**COVERAGE RATE**

Approximately 3.5 to 4 m<sup>2</sup> /Ltr/Coat, depending upon surface texture, porosity and absorption of concrete. Generally 2-4 coats are required.

**CURING**

Conpatch NCI does not require any special curing and if required can be opened for traffic after a few minutes of application.

**PACKAGING**

25 Ltr pails and 200 Ltr drums.

**LIMITATIONS**

Before and after application the surface should be protected from rain, frost and direct sunlight. Application should be done above freezing point.

*NOTE : For complete and entire concrete corrosion protection system please contact Cormix Technical Department.*

**STORAGE CONDITIONS & SHELF LIFE**

Store in the shade do not allow to freeze. Shelf life is 12 months in original sealed containers. Stir before application.

**HEALTH & SAFETY**

**Eye contact:** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention urgently.

**Skin contact:** Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. If vomiting occurs naturally, lean victim forward to reduce risk of aspiration.

Obtain medical attention urgently

**Inhalation:** Remove from exposure. In cases of possible respiratory irritation or if feeling unwell due to prolonged exposure, obtain medical attention.

**TECHNICAL SERVICE**

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

**QUALITY ASSURANCE**

ISO 9001 : 2008 verified by TUV Nord

**CONTACT DETAILS**

**Exclusive Distributor for Cormix International Ltd.**

**CREST CORMIX PTY. LTD.**

13 Newmarket Lane, Epping, Victoria 3076, Australia

Tel. +61 3 9945 2700

Fax. +61 3 9945 2799

<http://www.crestcormix.com.au>

E-mail: [enquiries@crestcormix.com.au](mailto:enquiries@crestcormix.com.au)