
TECHNICAL DATA SHEET

Product name: Black/White D06X-0-D4V

This protective film can be used to protect sensitive surfaces against mechanical damage and dust or dirt in transport transit, storage and assembly.

Main usages

Outdoor & Indoor Protection for the following surfaces with:

- Aluminium
- Stainless Steel
- Ceramics & Marble
- Polyester, PUR, Acrylic Lacquers & Plastics

Technical data

Type of film	LDPE UV Stabilised
Colour	Black/White
Thickness	60µm ± 5 µm
Elongation	>200%
Type of Adhesive	Acrylic Disp.
Adhesion strength	1.2 - 2.0 N/50mm

Application

- Surfaces to be protected should be dry, free from dust, oil, solvents or other chemicals.
- The best results are obtained with temperature of surface and surroundings at **+15°C to 40°C**.
- Use laminating machines with rubber coated press rollers.
- Try to eliminate or minimise film elongation, and the formation of air bubbles and folds during lamination.
- Removing the film is advisable to perform in the temperature range **5°C to 40°C** (Not below 5°C).
- The film is not suitable for extreme thermoforming.

D06X-0-D4V Film is fully recyclable

Note

All data are average values. We suggest test this material with the surface and material to be protected, to ensure the suitability for the intended application.

We reserve the right to improve products and change specifications, without prior notice which may alter the performance. Claims for compensation only exist in scale of our sale, delivery and payment conditions.

CREST CORMIX PTY LTD

1/111 Lewis Road, Koxfield Victoria 3180, Australia. Tel. +61 3 9887 0422
<http://www.crestcormix.com.au> E-mail: enquiries@crestcormix.com.au