

TECHNICAL DATA SHEET

Product name: Fine Line Adhesive Tape

Application

Fine Line Masking for the OEM Automotive and General Metal Surfaces where precise masking and higher temperatures are involved up to 140°C. Adheres well to a variety of surfaces, handles compound curves and detail work - clean removability after low bake cycle.

Rolls Sizes Available: 3mm to 1 metre Width (Can be cut to size).

Rolls Length : 55 Metres (Standard)

Technical data

Type of film	Thermostabilised cadmium free Polymerfoil 0.10mm with Rubber Blend Adhesive Conformable and Solvent Resistant.
Colour	Green
Thickness	0.13mm
Elongation at Break	>150%
Service Temperature	-30°C to 140°C
Adhesion strength	2.0 N/cm

Storage Temperature

15°C to 35°C.

Surface Preparation

The surfaces on which the tape is to be used must be clean, dry, free from dust, oil, solvents or other chemicals. Remember that pressure sensitive adhesive tape must be applied with the maximum possible pressure in order to achieve maximum adhesion levels.

Recommended application temperature is between **15°C to 35°C**

Fine Line Adhesive Tape is fully recyclable.

Note

All data are average values. We suggest test this material with the surface and material to be protected, to ensure the suitability for the intended application.

We reserve the right to improve products and change specifications, without prior notice which may alter the performance. Claims for compensation only exist in scale of our sale, delivery and payment conditions.

CREST CORMIX PTY LTD

1/111 Lewis Road, Knoxfield, Victoria 3180, Australia. Tel. +61 3 9887 0422
<http://www.crestcormix.com.au> E-mail: enquiries@crestcormix.com.au