

---

## TECHNICAL DATA SHEET

### Product name: **Grey/Grey or Black/Grey L10X-0-C6F**

This protective film can be used to protect glass surfaces against mechanical damage and dust or dirt in transportation, storage and during the assembly process.

#### Main usages

Outdoor & Indoor Protection Film for the following surfaces with low gloss:

- Aluminium (Ground, Matt or Anodised).
- Stainless Steel.
- Powder Coated metallic surfaces.
- High Grade Steel.
- *This film is suitable for laser cutting (Co2 & Fibre).*  
*(Not suitable for Copper or Brass).*

#### Technical data

Type of film	LDPE
Colour	Grey/Grey or Black/Grey
Thickness	95µm ± 8µm
Elongation	>240%
Type of Adhesive	Natural Rubber
Adhesion strength	6.5 - 9.5 N/50mm (Stainless Steel)

*This film may contain print "laser"*

#### Application

- Surfaces to be protected should be dry, free from dust, oil, solvents or other chemicals.
- Adhesive layer is not water resistant.
- Use laminating machines with rubber coated press rollers.
- Try to eliminate or minimize film elongation, and the formation of air bubbles and folds during lamination.
- Removing the film is advisable to perform in the temperature range **5°C to 40°C** (Not below 5°C).
- The film is not suitable for extreme thermoforming.

L10X-0-C6F Film is fully recyclable.

#### Note

All data are average values. We suggest test this material with the surface and material to be protected, to ensure the suitability for the intended application.

We reserve the right to improve products and change specifications, without prior notice which may alter the performance. Claims for compensation only exist in scale of our sale, delivery and payment conditions.

### **CREST CORMIX PTY LTD**

1/111 Lewis Road, Knoxfield, Victoria 3180, Australia. Tel. +61 3 9887 0422  
www.crestcormix.com.au E-mail: enquiries@crestcormix.com.au