

MOBIHEL®

... for the cars we love

PE PUTTY FINI

Two-component polyester fine levelling out mass to even out smaller irregularities after the sealer application (holes, scratches etc.).

Distributed by:

Crest Cormix Pty. Ltd.

13 Newmarket Lane,

Epping, Victoria 3076.

Tel: +61 3 9945 2700

Fax: +61 3 9945 2799

Email: enquiries@crestcormix.com.au

Web: www.crestcormix.com.au

HELIOS TBLUS, d.o.o., Količevo 65, 1230 Domžale, Slovenija

T: +386 1 722 40 00, E: office@helios-refinish.com, www.mobihel-refinish.com



PACKING DATA

Packing:
12 x 1.0 kg

Index:
40786932

HYGIENE & PERSONAL PROTECTION



TECHNICAL CHARACTERISTICS

	MOBIHEL PE PUTTY FINI	HARDENER
Colour:	Light grey	Red
Product type:	Polyester resin	Peroxide
Density:	1,799 kg/l	1,2 kg/l



2004/42/II B(a) (780) 720
EU limit value VOC for this type of products (category II B (a)) in the form, which is ready for application is 250 g/l VOC of this product, prepared for use is 170 g/l.

SUBSTRATE

it is always applied only to a suitably prepared filler

PRODUCT PREPARATION/MIXING



Mixing ratio: 100 g MOBIHEL PE PUTTY FINI
2 g BP Hardener



Pot life of the mixture at 20°: 7 - 10 min/20°C



Stir well

APPLICATION



Spreading

DRYING



Drying time at 20°C: 20 – 30 min



Drying time (infra-red short-wave): 5 min
Distance to the object: 70 - 80 cm

SANDING



Dry sanding: P360 – P400



Wet sanding:

P600 – P800

FURTHER TREATMENT



Further treatment:

All 2K fillers from MOBIHEL program
All topcoat from MOBIHEL program

SHELF LIFE



Shelf life:

18 months

SAFETY ADVICE

Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. In case of fire: use powder, foam or CO2 for extinction.

ONLY FOR PROFESSIONAL USE