

---

## **TECHNICAL DATA SHEET**

**Product name: Clear Transparent N05T-0-R1V**

This protective film can be used to protect sensitive surfaces against mechanical damage and dust or dirt in transportation, storage, and during the assembly process.

### **Main usages**

Protection Film for the following surfaces:

- Smooth & glossy surfaces.
- Hard smooth PVC.
- Glossy pre-painted metal sheets.
- Stainless Steel.

### **Technical data**

Type of film	LDPE UV Stabilised
Colour	Clear, Transparent
Thickness	50µm ± 5 µm
Elongation	>280%
Type of Adhesive	Acrylic Disp
Adhesion strength	2.4 - 4.0 N/50mm

### **Application**

- Surfaces to be protected should be dry, free from dust, oil, solvents or other chemicals.
- Adhesive layer is not water resistant.
- Use laminating machines with rubber coated press rollers.
- Try to eliminate or minimize film elongation, and the formation of air bubbles and folds during lamination.
- Removing the film is advisable to perform in the temperature range **5°C to 40°C** (Not below 5°C).
- The film is not suitable for extreme thermoforming.

N05T-0-R1V Film is fully recyclable.

### **Note**

All data are average values. We suggest test this material with the surface and material to be protected, to ensure the suitability for the intended application.

We reserve the right to improve products and change specifications, without prior notice which may alter the performance. Claims for compensation only exist in scale of our sale, delivery and payment conditions.

---

### **CREST CORMIX PTY LTD**

1/111 Lewis Road, Knoxfield Victoria 3180, Australia. Tel. +61 3 9887 0422  
<http://www.crestcormix.com.au> E-mail: [enquiries@crestcormix.com.au](mailto:enquiries@crestcormix.com.au)