

SMART

Your car refinish solution

SOFT PUTTY

Two-component polyester soft putty for filling deep, uneven areas. Specially formulated to ensure very good filling characteristics and a very easy sanding this putty is especially recommended for large surfaces. It has a finer structure to ensure a pore free surface after application and is not shrinking in time.



Distributed by:

Crest Cormix Pty. Ltd.
13 Newmarket Lane,
Epping, Victoria 3076.

Tel: +61 3 9945 2700

Fax: +61 3 9945 2799

Email: enquiries@crestcormix.com.au

Web: www.crestcormix.com.au

HELIOS TBLUS, d.o.o., Količevo 65, 1230 Domžale, Slovenija

T: +386 (0)1 722 40 00, E: office@helios-refinish.com, W: www.helios-refinish.com

PACKING DATA	Packing: 12 x 0.5 kg 12 x 1.0 kg 6 x 1.8 kg		Index: 47902701 47902702 47902703	
HYGIENE & PERSONAL PROTECTION	<div><div></div><div></div><div></div><div></div><div></div></div>			
TECHNICAL CHARACTERISTICS	S.M.A.R.T. SOFT PUTTY		HARDENER	
	Colour:	Beige	Red	
	Product type:	Polyester resin	Peroxide	
	Density:	1.801 kg/l	1.2 kg/l	
		2004/42/II B(b) (250) 170: EU limit value VOC for this type of product (category II B (b)) in the form, which is ready for application is 250 g/l. VOC of this product, prepared for use is 170 g/l.		
SUBSTRATE	Steel sheet metal Other polyester putties 2K fillers			
SUBSTRATE PREPARATION	All substrates must be thoroughly sanded and cleaned with S.M.A.R.T. SILICONE CLEANER prior to application. Polyester products should be coated with 2K fillers/primers to avoid peroxide transfer into the subsequent coats.			
PRODUCT PREPARATION/MIXING		Mixing ratio:	100 g S.M.A.R.T. SOFT PUTTY 2 g BP Hardener	
		Pot life of the mixture at 20°:	3 - 6 min	
		Stir well		
APPLICATION		Spreading		
DRYING		Drying time at 20°C:	20 - 30 min	
		Drying time (infra-red short-wave):	5 min Distance to the object: 70 - 80 cm	
		Dry sanding:	Rough sanding: P80 → P120 Fine sanding: P150 → P180 → P220	

FURTHER TREATMENT		Further treatment:	All 2K fillers
SHELF LIFE		Shelf life:	18 months
SAFETY ADVICE	<p>Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. In case of fire: use powder, foam or CO2 for extinction. Product contains organic solvents.</p> <p>ONLY FOR PROFESSIONAL USE</p>		