

BITUFLASH - BITUMEN FLASHING TAPE

Description

Self adhesive sealing tape with a bitumen base compound laminated by a re-inforced aluminium film Available in various colours on special orders, widths and lengths.

Uses

- General flashing applications for dielectric insulation.
- Multi purpose sealing, repairing gutters, most types of roofing, pipes, sky lights

Advantages

- Excellent dielectric insulation
- Easy application for high technical use.
- Excellent resistance against UV rays

Technical Support

CREST CORMIX comprehensive technical support, including help at the design stage, application advice and on site problem solving. Specifiers and contractors are encouraged to contact our staff for answers to their questions.



Technical Data

CHARACTERISTICS	VALUE	TEST
Thickness	1.1 mm	-
U.V. Resistance	Resistant	-
Tensile Strength (N/25mm)	134	ASTM D 1000
Elongation (%)	91	ASTM D 1000
Adhesion Steel (180°Peel,N/25mm)	75	ASTM D 1000
Vertical Flow (6 hrs 80°C)	4	-
Application Temperature	+5°C / +45°C	-
Service Temperature	-40°C / +80°C	-

CREST CORMIX PTY LTD
Factory 1/111 Lewis Road, Knoxfield, Melbourne VIC 3180
Ph: +61 3 9887 0422 A/Hours Mob: +61 406 343610
Email: enquiries@crestcormix.com.au **Web:** www.crestcormix.com.au

