



CREST
CORMIX

PRIMER B4

An integral Primer component of the ROADANCHOR® Road Tape System, providing for the sealing and reinforcement to crack repairs in concrete & asphalt surfaces, specific to roads, pavements and culverts.

DESCRIPTION:

PRIMER B4 is a proprietary blend of viscous bituminous resins and tackifiers dispersed in a refined hydrocarbon carrier.

USES:

PRIMER B4 is used as the pre-priming agent for ROADANCHOR® Bitumen Geotextile Roadseal Tape and other Crest Cormix Bitumen or Butyl Based remedial repair systems.

FEATURES:

- Fast Drying
- Highly resistant to Mineral acids, salts and alkalis
- Promotes high adhesion for Bitumen & Butyl Tape Systems
- Brush / Roller / Sponge/ Squeegee or spray applied
- Fills surface irregularities providing strong intercoat contact with bitumen or butyl tape compounds

APPLICATION:

Steel - prepare to ST2 (power brushed). Feather all edges of any existing coating, followed with degreasing using Crest Wax & Grease Remover.

Concrete & Asphalt – ensure surfaces are well cured and dry, removing all loose material from the surface.

Thoroughly stir **PRIMER B4** to ensure uniformity of mix. Apply an even coating at a rate of 8-10m²/ Litre.

PACKAGING:

20 Litre Pails

4 Litre Tins

PROPERTIES:

Specific Gravity - 0.94

Volume Solids – 62% (approx.)

Drying Time (Tack Dry) – 10-15 minutes @ 25°C

Coverage – 10-12 m² per Litre

Application Temp – minus 5°C to 55°C (*Best to apply above 10°C & below 45°C*)

Manufactured in Australia by:

CREST CORMIX PTY LTD

13-15 Apollo Drive, Hallam, Melbourne VIC 3803

PH: +61 3 9887 0422

Email: enquiries@crestcormix.com.au

www.crestcormix.com.au



Important Notice

CREST CORMIX products should be used in accordance with the information contained here. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained here is CREST CORMIX's best knowledge at the date of publication, CREST CORMIX PTY LTD makes no representation about the accuracy of the information and information provided is not intended as recommendations which infringe on other patents. If you need clarification or more information, you should contact CREST CORMIX PTY LTD directly. CREST CORMIX products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, CREST CORMIX PTY LTD accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of CREST CORMIX products or reliance upon the information contained here. These products are designed solely for use by fully qualified contractors utilizing specialized equipment and industry expertise.